MATERIAL SAFETY DATA SHEET

PRODUCT AND COMPANY IDENTIFICATION

Laxmi Agro Industrial Consultants & Exporters Limited 24/24, Rahul Apartments, Ansari Road, Daryaganj, New Delhi – 110002 Phone – 011 23279988, 23279022 Fax – 01123267919 Contact persons – Mr. UK Jha - Mr. Shiv Gupta Email – <u>laxmi@skgroup.org</u>; <u>shivgupta@skgroup.org</u>

I. <u>SUBSTANCE:</u>

TRADE NAME	: LABSA
COMMODITY CODE	: HSN 2904-10-90 / 3402-11-90
APPLICATION	: Intermediary for the production of detergent.

II. COMPOSITION / INFORMATION ON INGREDIENTS

: Substance
: Linear Alkyl Benzene Sulphonic Acid
: C6H4 (SO3H) (CS2)10CS3
: 27176-87-0
: 248-289-4
: Not Classified.

III. <u>HAZARDOUS IMPURITIES</u>

NAME	CONCENTR.	CAS N.	EC N.	SYMBOL
Sulphuric Acid	4-7% max	7664-93-9	016-020-00-8	C-Corrosive

IV. HAZARDS IDENTIFICATION

ADVERSE HUMAN HEALTH EFFECTS : The product is a corrosive substance. Contact With the eye may cause ocular lesions and Contact with wet skin may cause burns. It is seriously irritating to the mucous if swallowed. The product is harmful if ingested.

ENVIRONMENTAL EFFECTS	: The product is not classified as dangerous to the environment. The user is advised to use anyway good work practice an to avoid contamination of environment.
OTHER EFFECTS	: The product is a strong acid which reacts exothermically with bases. Dilution with water produces heat.
V. <u>FIRST AID MEASURES</u>	
INGESTION	: The product may cause severe irritation of the mouth and oesophagus. If accidentally ingested, administer water. Do not induce vomiting. Call a physician immediately.
INHALATION	: The product is not volatile. If under particular conditions such as in the case of fire, fumes or Aerosols are inhaled, remove the patient to a well ventilated location and call a physician.
EYE CONTACT	: Flush eyes immediately with running water for a long time. Seek medical assistance immediately.
SKIN CONTACT	: The product may cause burns. Remove the contaminated clothing and wash with plenty of water and call a physician immediately.
ANNOTATIONS TO A PHYSICIAN	: The product is a high foaming anionic surfactant. If gastric lavage is necessary, then use silicon antifoam (dimethicone).

VI. FIRE FIGHTING MEASURES

GENERAL INFORMATION	: The product poses little risk of ignition. If it happens to be involved in a fire, keep the tank cooled by means of a water spray in order to avoid decomposition of the product.
SUITABLE EXTINGUISHING MEDIA	: Water spray, foam, carbon dioxide.
NOT CHITADI E EVTINCIHCHING	Nono in nonticular

NOT SUITABLE EXTINGUISHING : None in particular. **MEDIA**

SPECIFIC HAZARDS	: Combustion produces carbon dioxide, carbon monoxide and oxides of Sulphur. When heated to decomposition, toxic fumes of SO2 and SO3 are emitted.

VII. ACCIDENTAL SPILL MEASURES

PERSONAL PRECAUTIONS : Avoid direct contact with the product. Wear rubber gloves and rubber boots, face shield and keep close by a gas mask provided with a filter for acid vapours.

- **ENVIRONMENTAL PRECAUTIONS**: Surround the spill with earth or sand. Collect the spilled material in suitable containers; if necessary absorb the spill into inert materials. Dispose of material according to the requirements of local law. In case of leaking into the sewer, inform the local authorities.
- METHODS FOR CLEANING UP : Neutralise the residue of the product with NaOH or with caustic lime. Wash the contaminated area with plenty of water. If excessive foam is produced, use silicon based antifoam to bring it down.

VIII. <u>HANDLING AND STORAGE</u>

HANDLING : Avoid contact with the product. While handling the product, wear a protective apron, rubber or PVC gloves and a face shield. Handle the product in well ventilated areas. Neutralize with base under controlled conditions. Compatible materials are Stainless Steel, Mild Steel, and Plastic Materials. Incompatible with galvanised steel, aluminium and copper alloys.

IX. EXPOSURE CONTROLS / PERSONAL PROTECTION

PRECAUTIONARY MEASURES	: Installation of an eyewash fountain is recommended. Do not eat, drink onto the workplace. When handling the product use approved protective clothing, rubber or PVC gloves, and a face shield.
PERSONAL PROTECTIVE EQUIPMENT	: Wear safety goggles or a face shield and approved protective clothing.

SPECIAL EQUIPMENTS : For large fires, wear self contained breathing apparatus.

THRESHOLD LIMIT VALUE : Not established.

REQUIREMENTS FOR PERIODIC : Specific measures are not foreseen. **HEALTH CHECK UP**

X. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AT 20 DEGREE C	: Brown viscous liquid.
ODOUR	: Of Sulphur.
NOMINAL ACTIVE MATTER CON	IC. : ~ 90% m/m.
AVEREAGE MOLECULAR MASS	:~ 326
- Ethanol	: Not Compatible
MASS DENSITY AT 20 DEGREE C	: ~ 1.070 g/cm3
VISCOSITY AT 20 DEGREE C	: ~ 1500 – 2000 MPa.s.
MELTING RANGE	: ~ -10 DEGREE C.
BOILING POINT	: ~ 315 DEGREE C.
VAPOUR PRESSURE AT 20 C	: BELOW 0.15 (0.001 mm Hg)
VAPOUR DENSITY (Air = 1)	: Not Applicable to this Product.
FLASH POINT (PMcc)	: 210 DEGREE C.
AUTOIGNITION TEMPERATURE	: Not Applicable to this product.
DECOMPOSITION TEMPERATUR	E: > 100 DEGREE C.
Ph	:~2
EXPLOSION PROPERTIES	: Not pertinent to this product.
OXIDIZING PROPERTIES	: Not pertinent to this product.

XI. STABILITY AND REACTIVITY

HAZARDOUS DECOMPOSTION PRODUCTS	S: In case of overheating, sulphur oxides can be emitted.
CONDITIONS TO AVOID	: Do not heat above 90 degree centigrade.
MATERIALS TO AVOID	: Neutralization with bases under uncontrolled conditions.
INTENDED USE AND TRANSFORMATION	: The product may be neutralized under controlled conditions with the appropriate base to produce the corresponding salt.

XII. TOXICOLOGY INFORMATION

POSSIBLE ROUTES OF PENETRATION : Ingestion and contact.

INGESTION	: Corrosive substance, harmful for ingestion. Oral acute LD50 : $> 500 - 2000 \text{ mg/kg}$.
EYE CONTACT	: Severe eye irritant. It may cause irreversible damage to the eyes.
SKIN CONTACT	: Contact may cause ulcerations.
SENSITIZATION	: Not Sensitizing.
INHALATION	: Inhalation is possible only as an aerosol. Strong irritant to respiratory passages.

XIII. ECOLOGICAL INFORMATION

ENVIRONMENTAL DISTRIBUTION	: Water is likely to be the main transport medium for the chemical, to estimate its possible environmental distribution.
PRIMARY BIODEGRADABILITY	: > 90% (OECD screening test (sodium salt)). The surfactant fulfils the requisite minimum requirements of primary biodegradability.
ABIOTIC DEGRADABILITY	: Not available.
ECOTOXITY	: 2.49 mg O2/mg.

CHEMICAL OXYGEN DEMAND (COD) : Not available.

LOG P o/w	: Not applicable, surface active substance.	
BCF	: Insufficient available information.	

XIV. DISPOSAL CONSIDERATIONS

Dispose of product in authorised places / methods in observance with the current laws. It may be treated in a biological waste treatment plant.

XV. TRANSPORT INFORMATION

UN CLASSIFICATION NUMBER	: 2586
NAME OF THE DELIVERING PRODUCT	: Linear Alkyl Benzene Sulphonic Acid/LABSA90%
PACKING INSTRUCTION	: P001
PACKAGING GROUP	: III
CLASS	: 8
MARINE POLLUTANT	: NO
EMS NUMBER	: F-A, S-B

XVI. REGULATORY INFORMATION

CLASSIFICATION AND LABELLING

PROVISIONAL

SYMBOLS OF HAZARD:

RISK PHRASES

<u>R22 - Harmful if Swallowed</u> <u>R34 - Causes Burns</u>

<u>SAFETY ADVICES</u> <u>S26 - In case of contact with the eyes, rinse immediately with plenty of water and seek medical help.</u> <u>S28 - After contact with skin, wash immediately with plenty of water</u> <u>S36/37/39 - Wear suitable protective clothing, gloves and eye face protection.</u> The information contained in this MSDS sheet is based on the available knowledge at the time of compilation. This information was obtained from tests conducted by or for Laxmi Agro Industrial Consultants & Exporters Limited or extracted from the literature and is relative to the safety prescriptions and correct use of the product. Laxmi Agro Industrial Consultants & Exporters Limited assumes no responsibility for applications that are incorrect or improper or not in accordance with the information reported above.

For any application outside normal foreseen, it is advisable to ask information from Laxmi Agro Industrial Consultants & Exporters Limited.

The data provided herein do not constitute specifications of quality. This MSDS cancels and replaces any preceding release.